

Altro High Performance Adhesive Information

Product	Type and Application Guide	Coverage Guide (depending upon subfloor and application method)
Altrofix 15 Product code: ADH15K12	A single part high tack acrylic copolymer. Apply to dry dust-free subfloors	Approx. 35-40m ² per 12kg pack, depending on application and subfloor porosity
Altrofix 19 Product code: ADH19K10B (10kg) ADH19K5B (5kg)	Two part polyurethane adhesive. Apply to dry dust-free subfloors. Flooring may require weighting down and must not be trafficked while setting. After setting, this adhesive is not affected by spillage of water and most other liquids. Not suitable for vertical surfaces. N.B. Neutral colour, can be pigmented to special order	Average coverage 15-20m ² per 10kg pack and 7.5-10m ² per 5kg pack
Altrofix 25NF Product code: ADH25NF5L	Contact adhesive. Apply to dry dust-free subfloors, but not bituminous or asphalt surfaces. Floor can be used immediately after laying. Solvent content necessitates good ventilation during use. Should always be used for coving and vertical surfaces	Average coverage 10m ² per 5 litre unit
Altrofix 365 Product code: ADH3655L	A one part high tack acrylic adhesive. Apply to dry porous and impervious surfaces in areas not subject to spillage	Average coverage 24-35m ² per 5 litre unit
Clean Up Solvent Product code: MASCL	For removing adhesive spillage. N.B. Flammable. Care must be taken as excessive use will cause surface damage to the floor covering	n/a

Altro only approves the adhesives recommended here; always follow detailed application and usage instructions on data sheet or as supplied with adhesive. Alternative adhesives may be available from other suppliers which are suitable for bonding the Altro range

but due to the possibility of changes in formulation, we do not accept responsibility in the event of failure. Unit coverage of Altrofix adhesives will depend upon subfloor, trowel size etc. See full laying details for each floor product for complete recommendations.

For further information or technical advice
Tel: 01462 707600 Fax: 01462 707515 E-mail: enquiries@altro.co.uk



HIGH PERFORMANCE FLOORING

visit www.altrotransflor.com