



Altro Transflor

High Performance Clean Up Solvent

Part No. MASCL
Contains Acetone (Dimethyl Ketone)

General

Altro clean up solvent can be used to remove residue adhesive from the surface of Altro Transflor. It can also be used to remove small spillages of inks, paints and some dyes.

Care must be taken when using this material as excessive use will cause surface damage to the floorcovering. It is therefore recommended that you apply the solvent to a test sample of the flooring prior to applying it the affected area. Available in 250ml.

Method of Use

Apply the solvent onto a clean white rag or directly onto the affected area. Do not rub, but wipe up the residue onto the rag. Repeat application if necessary.

Health & Safety

- Repeated exposure may cause skin dryness and cracking.
- Vapours may cause drowsiness and dizziness.
- Irritant to eyes - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Keep container in a well ventilated place.
- Highly flammable - Keep away from sources of ignition.
- No smoking.
- Do not breathe vapour.
- Take precautionary measures against static discharges.

For further information see Altro Material Safety data sheet available from Altro Transflor, or visit www.altrotransflor.com.

For further information or technical advice contact your local Altro Transit representative, alternatively
Tel: +44 1462 480480 Fax: +44 1462 480010
E-mail: transflor@altro.co.uk

visit www.altrotransflor.com



HIGH PERFORMANCE FLOORING